

GFA115K



KEVLAR® THREAD LAMBSKIN LEATHER GRAIN GLOVE / 15-CM CUFF

Ref. GFA115K



Product specifications

Lambskin full grain leather. Cowhide split leather cuff. Kevlar® Technology seams. Fourchette assembly. 15 cm cuff. Length: 35 cm.

Hand : lambskin full grain leather (thickness: 0.7 to 0.9 mm).

Cuff : cowhide split leather.

Kevlar® sewn.

COLOUR

Grey

SIZE

10

Product Use - Risks



Heat



Wearing



Heavy industry

Product's highlights & user's benefits

Lambskin leather :
• Flexibility and dexterity

Kevlar® seams



Certifications and Standards



PPE DIRECTIVE 89/686/EEC

EN420:2003 General requirements

4: Dexterity (from 1 to 5)



EN388:2003 Protective gloves against mechanical Risks (Levels obtained on the palm)

2: Resistance to abrasion (from 1 to 4)
1: Resistance to cutting (from 1 to 5)
1: Resistance to tear (from 1 to 4)
1: Resistance to puncture (1 to 4)





EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

4: Resistance to flammability (from 1 to 4)
1: Resistance to contact heat (from 1 to 4)
x: Resistance to convective heat (from 1 to 4)
x: Resistance to radiant heat (from 1 to 4)
4: Resistance to small projections of liquid metal (from 1 to 4)
x: Resistance to large projections of molten metal (from 1 to 4)

EN12477:2001/A1:2005 Protective gloves for welders

B: Welding - High dexterity required Type B

References

| References | Bar code | COLOUR | SIZE |  |  |
|------------|---------------|--------|------|---|---|
| GFA115K10 | 3295249006129 | Grey | 10 | 120 | 12 |