

EX118200A



ADJUSTABLE POSITIONNING LANYARD VIA TENSIONER + 1 AM010

Ref. EX118



Product specifications

Adjustable work positioning lanyard via stainless steel tensioner. Adjustable length. Stranded rope Ø 14 mm equipped with a wear indicator. Thimble loop. Splice protection. Protective sheath. 1 hook.

Lanyard: Polyester.
Tensioner: Stainless steel.

COLOUR
Orange

SIZE
0.20 to 2 m, 0.20 to 4 m

Product Use - Risks



Fall



Agriculture / Green areas



Construction / Civil engineering



Second work /

craftman
energy



Heavy industry



Light industry



Oil / Gas



Mining



Wind



Work positioning



Restraint

Product's highlights & user's benefits

Recommended accessory for the proper use
of this product: 1 AM002 connector

Certifications and Standards



PPE DIRECTIVE 89/686/EEC



EN363 : 2008 Personal fall protection equipment - Personal fall protection systems

EN364 : 1992 Personal fall protection equipment : Test method

EN365 : 2004 General requirements for the instructions for use and the marking

EN358 Personal fall protection equipment for work positioning and prevention of falls from a height - Belts for work positioning and restraint and work positioning lanyards.

References

References	Bar code	COLOUR	SIZE		
EX118200A	3295249176785	Orange	0.20 to 2 m	5	-
EX118400A	3295249176792	Orange	0.20 to 4 m	5	-