

LO030



WEBBING LANYARD AND ANCHORAGE POINT - 2 M

Ref. LO030\_



#### Product specifications

Lanyard and anchorage point in tubular webbing. 2 sewn loops. Width 25 mm.

Polyamide.

**COLOUR**

Grey

**SIZE**

2 m

Product Use - Risks



Fall



Agriculture / Green areas



Construction / Civil engineering



Second work /



craftman



Heavy industry



Light industry



Services / Logistics



Oil / Gas



Mining



Wind energy



Long vertical movement or movement on inclined surface



Long vertical movement or

movement on inclined surface for rope access work



Short vertical movement or movement on

inclined surface (less than 3 m)



Long horizontal movement on horizontal surface



Long

horizontal movement on vertical structure



Short horizontal movement (less than 3 m)



Restraint



Rescue and evacuation

## Certifications and Standards



PPE DIRECTIVE 89/686/EEC

EN363 : 2008 Personal fall protection equipment - Personal fall protection systems

EN364 : 1992 Personal fall protection equipment : Test method



EN365 : 2004 General requirements for the instructions for use and the marking

EN795:2012 Personal fall protection equipment : Anchorage devices

B: Anchorage device type B

EN354 : 2010 Personal fall protection equipment - Lanyards.

## References

References	Bar code	COLOUR	SIZE		
LO030	3660348006019	Grey	2 m	15	-