

TIG15K



WELDER'S LEATHER GLOVE / 15 CM GAUNTLET.

Ref. TIG15K



Product specifications

Goatskin full grain leather. Cowhide split leather cuff. Kevlar® Technology sewn. American assembly. 15 cm cuff. Length: 35 cm.

Full grain leather. Cowhide gauntlet. Kevlar® thread sewn. Leather thickness: 0.80 to 1.00 mm.

COLOUR

Grey

SIZE

08, 09, 10

Product Use - Risks



Heat



Wearing



Heavy industry

Product's highlights & user's benefits

Goatskin leather :

- Flexibility, dexterity
- Very good mechanical resistance

Heat resistant welder gloves:

- Very good mechanical resistance
- Flame resistant, heat resistant and big molten metal spray



Certifications and Standards



PPE DIRECTIVE 89/686/EEC

EN420:2003 General requirements

- 5: Dexterity (from 1 to 5)



EN388:2003 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 2: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 2: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)



EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

- 4: Resistance to flammability (from 1 to 4)
- 1: Resistance to contact heat (from 1 to 4)
- x: Resistance to convective heat (from 1 to 4)
- x: Resistance to radiant heat (from 1 to 4)
- 4: Resistance to small projections of liquid metal (from 1 to 4)
- x: Resistance to large projections of molten metal (from 1 to 4)

EN12477:2001/A1:2005 Protective gloves for welders

- B: Welding - High dexterity required Type B

References

References	Bar code	COLOUR	SIZE		
TIG15K08	3295249033965	Grey	08	36	6
TIG15K09	3295249033972	Grey	09	36	6
TIG15K10	3295249033989	Grey	10	36	6