

## NITREX VE802



NITREX 802 NITRILE GLOVE

Ref. VE802



### Product specifications

Nitrile with cotton flocklining. Length: 33 cm. Thickness: 0,38 mm.

100% nitrile (NBR: Nitrile Butadiene Rubber)

Flocage : 100% cotton

Tested according to the standards EN374-2:2003 determination of penetration resistance (level 2, AQL<1,5) and EN374-3:2003 (AJKL) (\*) levels of permeation from 1 to 6 (A : Methanol = 3, J : n-Heptane = 6, K : Sodium hydroxyde 40% (NaOH) = 6, L : Sulphuric Acid 95%-98% = 4, Butanol = 6, Cyclohexane = 6, Di-isobutyl ketone = 5, Ethyl ether = 2, Ethylene glycol = 6, Formaldehyde 37% = 6, Hydrochloric acid 37% = 6, Iso octane = 6, Kerosene (Burning oil - 28 sec) = 6, Petroleum ether = 6, Tetrachloro ethylene = 5, Turpentine = 6, Super grade unleaded petrol (4 star - 98 octane) = 6, Methyl tert-butyl ether = 5, Amyl Acetate = 3, Chrystallisabel acetic acid = 3, Naphta solvent = 5, Dimethyl sulphoxide = 2).

#### COLOUR

Green

#### SIZE

6/7, 7/8, 8/9, 9/10, 10/11

## Product Use - Risks



Biological chemical particles



Wearing



Agriculture / Green areas environment



Heavy industry



Light industry



Hygiene

## Product's highlights & user's benefits



Raised pattern texture on palm and fingers :

- Anti-slip

Flocked lining :

- Absorbs perspiration
- Comfort



## Certifications and Standards



### PPE DIRECTIVE 89/686/EEC

#### EN420:2003 General requirements

5: Dexterity (from 1 to 5)



#### EN388:2003 Protective gloves against mechanical Risks (Levels obtained on the palm)

4: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

0: Resistance to tear (from 1 to 4)

1: Resistance to puncture (1 to 4)



#### EN374-2:2003 Protective gloves against chemicals and micro-organisms - Part 2: Determination of resistance to penetration



#### EN374-3:2003 Protective gloves against chemicals and micro-organisms - Part 3: Determination of resistance to permeation by chemicals

AJKL: Resistant gloves to permeation by chemicals, tested according to EN374-3

3 > 60 mn: Méthanol (A) CAS 67-56-1

6 > 480 mn: n-Heptane (J) CAS 142-85-5

6 > 480 mn: Caustic soda 40% (K) CAS 1310-73-2

4 > 120 mn: Sulphuric acid 96 % (L) CAS 7664-93-9





### REGULATION (EU) 1935/2004 CONTACT WITH FOOD PRODUCTS

#### GLOB MIGR Food contact - Overall Migration

:: Contact with any type of food

References

References	Bar code	COLOUR	SIZE		
VE802VE06	3295249011819	Green	6/7	120	12
VE802VE07	3295249011826	Green	7/8	120	12
VE802VE08	3295249011833	Green	8/9	120	12
VE802VE09	3295249011840	Green	9/10	120	12
VE802VE10	3295249012359	Green	10/11	120	12